


NEW TRIA® 68

recessed ceiling light, 1800-3000 K, 60°, IP 20, round, white

Discover the new generation of our NEW TRIA® recessed ceiling light with even more modularity for an individual lighting experience. Top sellers such as the NEW TRIA® 68 are available as a complete set. The integrated LED MODULE, which is available with dim-to-warm technology (1800-3000 K) and different beam angles (38°/60°), provides lighting design options. The pivot range allows flexible alignment of the light, in black or white, the high-quality housing blends harmoniously into any room ambience. And thanks to the 68 mm mounting ring supplied, the downlights can also be installed quickly and simply.



TECHNICAL DATA

Item no.	1007425
Rotating or tilting	tiltable
IP Code	IP20
Dimmable	Yes
Dimming technology	Leading edge,trailing edge
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	250 mA
Safety class	II
Wattage	11 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Number of luminaires at LS B16A	85
Number of luminaires at LS C16A	144
Level of inrush current	2 A
Duration of inrush current	30 µs
Lumen	70-700 lm
Colour temperature	1800-3000 Kelvin
Beam angle	60 °
Color	white
Service life	50000 h
Risk Group	1
Height	4 cm

Light Source

879017	

Diameter	8.2 cm
Net weight	0.219 kg
Gross weight	0.264 kg
Shape of cut-out	round
Installation depth	4.5 cm
Installation diameter	6.8 cm
BIG WHITE Page	109