


S-CUBE

wall and ceiling-mounted light, 2700/3000K, 15W, PHASE, 80°, anthracite

The new S-CUBE wall and ceiling-mounted light captivates with its modern and elegant design. Thanks to its adjustable light colour (2700/3000K), IP65 protection class, high colour rendering index (CRI>80), dimmability and long lifespan (L80/B10 50,000h), it provides everything you would expect from a high-quality outdoor light. The delicate satin finish of the LED cover is a real highlight, creating a clean, homogenous look and draws the gaze to the white reflectors.



TECHNICAL DATA

Item no.	1007458
IP Code	IP 65
Impact resistance class	IK 04
Impact resistance	0.2 Joule
Assembly	Surface
Assembly details	Ceiling,Wall
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	15 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	61
Number of luminaires at LS C16A	61
Level of inrush current	6.5 A
Duration of inrush current	40 µs
Temperature at glass (light emission)	60 °C
Stroboscopic effect (SVM)	0.02
Lumen	1000/1200 lm
Colour temperature	2700/3000 Kelvin

1807468	

Beam angle	80 °
Color	anthracite
CRI	80
LXXBXX data	L70B20
Service life	50000 h
Risk Group	0
Width	9.5 cm
Height	11 cm
Depth	11.1 cm
Net weight	1.1 kg
Gross weight	1.177 kg
BIG WHITE Page	805