


# INDUSTRY BATTEN V 1500

**22/42W 830/840/857**

Discover our new technical product range: SLVtec.With state-of-the-art LED technology, we offer energy-efficient and functional lighting solutions for indoor and outdoor use. From wet room lights to high-bay spotlights – our high-quality products impress with functionality and a fair price-performance ratio. These include the INDUSTRY BATTEN V light, which is adjustable in terms of output (22-W/41W), light colour (3000K/4000K/5700K) and light intensity (5220lm/5460/5760lm) via dip switches. Installation is easy thanks to the removable equipment rack, and electrical connection is possible without tools thanks to the integrated pressure clamp. Decide in favour of SLVtec today.




## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1007507 |
| **IP Code** | IP 20 |
| **Impact resistance class** | IK 04 |
| **Impact resistance** | 0.5 Joule |
| **Assembly** | Surface |
| **Assembly details** | Ceiling,Wall |
| **Primary nominal voltage** | 220-240V ~50/60Hz |
| **Secondary power / voltage** | 500/960 mA |
| **Safety class** | I |
| **Wattage** | 42 W |
| **Minimum ambient temperature** | -20 °C |
| **Maximum ambient temperature** | 40 °C |
| **Operating efficiency (LOR)** | 0,94 |
| **Number of luminaires at LS B16A** | 13 |
| **Number of luminaires at LS C16A** | 20 |
| **Level of inrush current** | 9.33 A |
| **Duration of inrush current** | 850 µs |
| **Stroboscopic effect (SVM)** | 0.02 |
| **Lumen** | 5220/5760/5460 lm |
| **Colour temperature** | 3000/4000/5700 Kelvin |
| **Beam angle** | 150 ° |
| **Color** | white |

| | |
|---|---|
| 1807495 |  |

| | |
|---|---|
| **CRI** | 80 |
| **LXXBXX data** | L70B50 |
| **Service life** | 50000 h |
| **Risk Group** | 0 |
| **Length** | 152 cm |
| **Width** | 6.1 cm |
| **Height** | 7 cm |
| **Net weight** | 1.55 kg |
| **Gross weight** | 1.659 kg |