


UNIVERSAL TRACKSPOT V 3Ph.

10/15/20 W 927/930/940 24°-60° white

Discover our new technical product range: SLVtec.With state-of-the-art LED technology, we offer energy-efficient and functional lighting solutions for indoor and outdoor use. From wet room lights to high-bay spotlights – our high-quality products impress with functionality and a fair price-performance ratio. These include the minimalist UNIVERSAL TRACKSPOT V three-phase spotlight, whose light colour (2700 K/3000 K/400 K) and light intensity can be adjusted via dip switches. Thanks to the multi-zoom function, the beam angle is also variable – from 24°, ideal for accent lighting, to 60° for homogeneous illumination. In addition, the high CRI >90 ensures the most lifelike color reproduction possible. Decide in favour of SLVtec today.



TECHNICAL DATA

Item no.	1007654
Rotating or tilting	rotary bar and tiltable
IP Code	IP20
Impact resistance class	IK 05
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	240/380/500 mA
Safety class	I
Wattage	20 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Level of inrush current	9.46 A
Duration of inrush current	1210 µs
Lumen	1800/1980/1920 lm
Colour temperature	2700/3000/4000 Kelvin
Beam angle	24 °
Color	white/white
CRI	90
Service life	50000 h
Risk Group	1
Length	14.5 cm
Height	13.5 cm
Diameter	7.2 cm

1807499	

Net weight	0.563 kg
Gross weight	0.772 kg
BIG WHITE Page	1002