



NOBLO® SPOT | 1Ph., Triple Track Set

NOBLO® SPOT, track system set, round, 2700 K, 19 W, trailing-edge phase, 32°, black

With the NOBLO® SPOT track system set you get everything you need for the perfect start. The set, available in several colour versions, includes two track sections, a central connector, two end caps and three NOBLO® SPOTS of the latest generation: high-quality spotlights made of aluminium with an improved CRI value (CRI >90), a lumen output of up to 126 lm/W and an increased service life of up to 50,000 hours. It's clear: with the new NOBLO® SPOTS, you are opting for a unique lighting experience.

Light source

1491914	A B

Item no.	1007673
Lamps included	No
Number of different light outlets	3
Rotating or tilting	rotary bar and tiltable
IP Code	IP20
Dimmable	true
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	150 mA
Safety class	I
Wattage	19 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	128.0
Number of luminaires at LS C16A	160.0
Level of inrush current	3.5 A
Duration of inrush current	120 µs
Beam angle	32°
Color	black
CRI	90
LXXBXX data	L80B10
Service life	50 000 h
Risk Group	1
Length	200 cm
Width	5 cm
Height	12.5 cm
Net weight	1.83 kg
Gross weight	2.61 kg
BIG WHITE Page	521