


# D-RING M

**wall light, PHASE, 2700/3000K, PHASE, IP65, black**

The new D-RING family elegantly picks up on the trend towards organic shapes. The dimmable indirect warm white light (2700K / 3000K), which can be adjusted via a CCT switch, discreetly and glare-free sets the scene for the facades. The two different diameters offer plenty of creative scope. Thanks to the special surface treatment, it can also be used near the coast.




## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1007913 |
| **IP Code** | IP65 |
| **Impact resistance class** | IK 06 |
| **Assembly** | Surface |
| **Assembly details** | Wall |
| **Dimmable** | Yes |
| **Dimming technology** | Leading edge,trailing edge |
| **Number of through-wires** | 80 |
| **Primary nominal voltage** | 220-240V ~50Hz |
| **Secondary power / voltage** | 190 mA |
| **Safety class** | I |
| **Wattage** | 15 W |
| **Minimum ambient temperature** | -20 °C |
| **Maximum ambient temperature** | 45 °C |
| **Number of luminaires at LS B16A** | 119 |
| **Number of luminaires at LS C16A** | 119 |
| **Level of inrush current** | 2.32 A |
| **Duration of inrush current** | 67.4 µs |
| **Stroboscopic effect (SVM)** | 0.01 |
| **Lumen** | 1260/1360 lm |
| **Colour temperature** | 2700/3000 Kelvin |
| **Color** | black |

| | |
|---|---|
| 1907087 |  |

| | |
|---|---|
| **CRI** | 80 |
| **LXXBXX data** | L80B20 |
| **Service life** | 50000 h |
| **Risk Group** | 1 |
| **Depth** | 5 cm |
| **Diameter** | 25 cm |
| **Net weight** | 1 kg |
| **Gross weight** | 1.07 kg |