


# T-TUBE

**wall-mounted light, GU10, double, sensor, IP44, max. 10 W, black**

The T-TUBE series of lights extends the successful TUBE family with a particularly slim, modern design variant for outdoor use. Available as a wall light or bollard light, it offers maximum design freedom with one or two GU10 lamps - ideal for pathways, entrances or terraces. Thanks to a special surface coating, T-TUBE is resistant to sea air and can therefore be used near the coast. The versions without a sensor have protection class IP65, while the sensor versions are labelled IP44. Their integrated motion sensors enable maximum efficiency and on-demand lighting control. A particular highlight is the integrated primary/replica functionality of the bollard lamps. This means that one light can act as the controlling element, while other lights are automatically switched on via through-wiring - ideal for a continuous line of light along driveways or footpaths.




## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1008011 |
| **Socket** | GU10 |
| **Number of sockets** | 1 |
| **Socket 2** | GU10 |
| **Number of sockets 2** | 1 |
| **Horizontal rotation range** | 90 ° |
| **IP Code** | IP44 |
| **Impact resistance class** | IK 06 |
| **Impact resistance** | 1 Joule |
| **Assembly** | Surface |
| **Assembly details** | Wall |
| **Primary nominal voltage** | 220-240V ~50/60 Hz |
| **Safety class** | I |
| **Wattage** | 10 W |
| **Minimum ambient temperature** | -20 °C |
| **Maximum ambient temperature** | 40 °C |
| **Temperature at glass (light emission)** | 60 °C |
| **Color** | black |
| **Width** | 10.1 cm |
| **Height** | 43.3 cm |
| **Depth** | 18 cm |
| **Net weight** | 1.42 kg |

| | |
|---|---|
| **Gross weight** | 1.48 kg |
| **BIG WHITE Page** | 908 |

## Recommended lamp

| | |
|---|---|
| **1005077** | LED lightbulb QPAR51 , GU10, 2700 K, black |