





ONE LINEAR 70

wall-mounted light, UP/DOWN, 2700/3000K, PHASE, brass

ONE LINEAR extends the popular SLV luminaire family with high-quality wall luminaires that are available in two new lengths (50 cm and 70 cm). The up/down lighting with an adjustable colour temperature (2700K/3000K) and the PHASE dimming function conjures up an extremely elegant and flexible lighting mood. Thanks to its IP44 protection rating, the ONE LINEAR wall light is a stylish highlight not only in hotels, restaurants and living rooms, but also in bathrooms.



TECHNICAL DATA

Item no.	1008083
Number of different light outlets	2
IP Code	IP44
Assembly	Surface
Assembly details	Wall
Dimmable	Yes
Dimming technology	Leading edge,trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	20 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Number of luminaires at LS B16A	114
Number of luminaires at LS C16A	114
Level of inrush current	5 A
Duration of inrush current	100 µs
Stroboscopic effect (SVM)	0.4
Lumen	1250/1350 lm
Colour temperature	2700/3000 Kelvin
Beam angle	120 °
Color	matt white/matt brass

1679802	

CRI	90
LXXBXX data	L80B10
Service life	50000 h
Risk Group	1
Width	70.5 cm
Height	4.2 cm
Depth	8.1 cm
Net weight	0.92 kg
Gross weight	1 kg