



ONE LINEAR 50

wall-mounted light, UP/DOWN, 2700/3000K, PHASE, brass

ONE LINEAR extends the popular SLV luminaire family with high-quality wall luminaires that are available in two new lengths (50 cm and 70 cm). The up/down lighting with an adjustable colour temperature (2700K/3000K) and the PHASE dimming function conjures up an extremely elegant and flexible lighting mood. Thanks to its IP44 protection rating, the ONE LINEAR wall light is a stylish highlight not only in hotels, restaurants and living rooms, but also in bathrooms.



TECHNICAL DATA

Item no.	1008086
Number of different light outlets	2
IP Code	IP44
Assembly	Surface
Assembly details	Wall
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	14 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Number of luminaires at LS B16A	160
Number of luminaires at LS C16A	160
Level of inrush current	5 A
Duration of inrush current	100 µs
Stroboscopic effect (SVM)	0.4
Lumen	900/1000 lm
Colour temperature	2700/3000 Kelvin
Beam angle	120 °
Color	matt white/matt brass

1679804	

CRI	90
LXXBXX data	L80B10
Service life	50000 h
Risk Group	1
Width	52.5 cm
Height	4.2 cm
Depth	8.1 cm
Net weight	0.77 kg
Gross weight	0.85 kg