


BRICK MESH

recessed wall light, rectangular, 3000K, 5W, IP55, black

Do you want to illuminate stairs, entrances, ramps or paths without glare? The BRICK Mesh recessed wall light produces light optimised for orientation that is extremely durable and weatherproof with a service life of 50,000 hours and an IP65 protection rating. As the luminaire body is installed completely inside the wall via a recessed pot, there is no risk of accidents. The otherwise closed knock-out openings on the side or rear ensure that the housing is not soiled when installed in concrete walls.



TECHNICAL DATA

Item no.	1008481
IP Code	IP65
Impact resistance class	IK 08
Impact resistance	5 Joule
Assembly	Recessed
Number of through-wires	64
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	5 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	64
Number of luminaires at LS C16A	102
Level of inrush current	15 A
Duration of inrush current	200 µs
Temperature at glass (light emission)	60 °C
Lumen	150 lm
Colour temperature	3000 Kelvin
Color	stainless steel
CRI	80
Service life	50000 h

Risk Group	1
Length	26 cm
Width	11 cm
Height	7.6 cm
Net weight	1.24 kg
Gross weight	1.34 kg
Shape of cut-out	rectangular
Installation length	25.2 cm
Installation width	7.5 cm
Installation depth	10.7 cm