


HIGHBAY C

340 60/80/100W 840 IP65

Discover our technical product range: SLVtec. With state-of-the-art LED technology, we offer energy-efficient and functional lighting solutions for indoor and outdoor use. From wet room lights to high-bay spotlights – our high-quality products impress with functionality and a fair price-performance ratio. These include the HIGHBAY product family, which is available in two sizes (340 and 400 mm diameter) and also as a DALI version with the HIGHBAY C 400. They impress with their efficiency of >175 lm/W and the two luminaires without DALI control can also be supplemented with sensors and a CASAMBI module for intelligent lighting control.



TECHNICAL DATA

Item no.	1008525
Number of different light outlets	1
IP Code	IP65
Impact resistance class	IK 08
Impact resistance	5 Joule
Assembly	Surface
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	260/350/440 mA
Safety class	I
Wattage	55 W
Minimum ambient temperature	-30 °C
Maximum ambient temperature	50 °C
Number of luminaires at LS B16A	16
Number of luminaires at LS C16A	27
Level of inrush current	58 A
Duration of inrush current	130 µs
Lumen	9700/13650/17500 lm
Colour temperature	4000 Kelvin
Color	black
CRI	80
UGR ≤	22
Service life	50000 h

Risk Group	1
Height	11.8 cm
Diameter	34 cm
Net weight	2.7 kg
Gross weight	3.8 kg

Accessories

1008529	Highbay C , 340 PC re-flector
1008532	HIGHBAY C , PIR sensor
1008531	HIGHBAY C , HF sensor
1008576	HIGHBAY C , CASAMBI module
1008528	HIGHBAY C , U-bracket