


# KADUX

**recessed ceiling light, double, 3000K, DALI 2, touch, 30°, white**

Experience high light output and efficiency for use in shops and retail environments: KADUX is our gimbal-mounted recessed ceiling luminaire, available as a single or double-lamp version in white or black and various colour temperatures (3000K/4000K). Thanks to the quick-connection box in a closed steel housing, the light is easy to install and is both robust and durable.




## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1008571 |
| **Number of different light outlets** | 2 |
| **IP Code** | IP20 |
| **Assembly** | Recessed |
| **Dimmable** | Yes |
| **Dimming technology** | DALI,Touch |
| **Primary nominal voltage** | 220-240V ~50/60 Hz |
| **Secondary power / voltage** | 1400 |
| **Safety class** | II |
| **Wattage** | 54 W |
| **Ambient temperature** | 80 °C |
| **Minimum ambient temperature** | -20 °C |
| **Maximum ambient temperature** | 40 °C |
| **Number of luminaires at LS B16A** | 37 |
| **Number of luminaires at LS C16A** | 74 |
| **Level of inrush current** | 65 A |
| **Duration of inrush current** | 100 µs |
| **Lumen** | 3150 lm |
| **Colour temperature** | 3000 Kelvin |
| **Color** | white/black |
| **CRI** | 90 |
| **Binning** | 6 SDCM |

| | |
|---|---|
| **Service life** | 50000 h |
| **Risk Group** | 1 |
| **Length** | 37 cm |
| **Width** | 19.5 cm |
| **Height** | 12.5 cm |
| **Net weight** | 2.8 kg |
| **Gross weight** | 3.24 kg |
| **Shape of cut-out** | square |
| **Installation length** | 34.5 cm |
| **Installation width** | 17 cm |
| **Installation depth** | 12.5 cm |