


# MEDO® RING 90

**pendant light, pendant length 300cm, 3000/4000K, 110°, PHASE, white**

The best MEDO® of all time is now also available as a pendant light in an elegant design: the MEDO® RING impresses with a longer service life and better energy efficiency of over 120 lm/W. It is available in two sizes and two colours, and can be controlled via trailing edge or DALI. The CCT switch (3000K/4000K) allows the light temperature to be selected as desired.




## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1008596 |
| **IP Code** | IP20 |
| **Assembly** | Surface |
| **Dimmable** | Yes |
| **Dimming technology** | trailing edge |
| **Number of through-wires** | 30 |
| **Primary nominal voltage** | 220-240V ~50/60 Hz |
| **Secondary power / voltage** | 1200 mA |
| **Safety class** | I |
| **Wattage** | 43 W |
| **Minimum ambient temperature** | -20 °C |
| **Maximum ambient temperature** | 45 °C |
| **Number of luminaires at LS B16A** | 50 |
| **Number of luminaires at LS C16A** | 50 |
| **Level of inrush current** | 5 A |
| **Duration of inrush current** | 300 µs |
| **Temperature at glass (light emission)** | 32 °C |
| **Lumen** | 5000/5300 lm |
| **Colour temperature** | 3000/4000 Kelvin |
| **Color** | white |
| **CRI** | 90 |
| **UGR ≤** | 25 |

| | |
|---|---|
| **Service life** | 50000 h |
| **Height** | 7 cm |
| **Diameter** | 90 cm |
| **Pendant length** | 300 cm |
| **Net weight** | 5.98 kg |
| **Gross weight** | 9.5 kg |