


ORDI II

WL, Wall-mounted light, Square, 2200/3000 K, IP65, White

The ORDI II wall-mounted light is an extension to the successful ORDI family and sets new standards in design and technology. With an optimised design, it offers improved technical specifications such as an IP65 protection rating, a sea-air resistant coating, and a robust IK07 classification. These properties make the light ideal for outdoor use, even under extreme conditions such as rain, wind, or salty air. Thanks to the CCT switch, the colour temperature can be flexibly adjusted. The insect-friendly 2,200 K is less attractive to insects due to its lower proportion of blue, while 3,000 K is suitable for functional lighting. The light has an impressive service life of 50,000 hours and is available in black and white. The dimmable versions of the ORDI II wall-mounted light allow the flexible adjustment of the light intensity, for a customised lighting concept.



TECHNICAL DATA

Item no.	1008722
IP Code	IP65
Impact resistance class	IK 07
Impact resistance	2 Joule
Assembly	Surface
Assembly details	Wall
Dimmable	Yes
Dimming technology	Leading edge,trailing edge
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	240 mA
Safety class	I
Wattage	9.5 W
Minimum ambient temperature	-25 °C
Maximum ambient temperature	45 °C
Number of luminaires at LS B16A	210
Number of luminaires at LS C16A	210
Level of inrush current	4.1 A
Duration of inrush current	81 µs
Temperature at glass (light emission)	55 °C
Lumen	750 / 900 lm
Colour temperature	2200/3000 Kelvin
Color	white

2261485	

CRI	80
Service life	50000 h
Risk Group	0
Width	18 cm
Height	16.2 cm
Depth	11.8 cm
Net weight	1.31 kg
Gross weight	1.48 kg
BIG WHITE Page	916