


TRACKSPOT V 3 Ph. 32W 930 50°

Black

Compatible with S-Track and Eutrac systems, the TRACKSPOT V 3-phase spotlight is the perfect choice for price-conscious commercial projects with demanding quality requirements. is the perfect choice for price-conscious commercial projects with moderate quality requirements. With an energy efficiency of over 120 lm/W, excellent colour rendering with CRI 90, and a high luminous flux of up to 4,000 lumens, the luminaire is ideal for applications where lighting quality and cost efficiency are crucial. Thanks to a service life of 50,000 hours (L80B50), the TRACKSPOT V guarantees a long-term lighting solution. Available in different versions with 18W or 32W, beam angles of 36° or 50°, and in 3,000 K or 4,000 K, the TRACKSPOT V offers the right solution for every project. The black and white colour variants enable harmonious integration into different room concepts.



TECHNICAL DATA

Item no.	1008855
Number of different light outlets	1
IP Code	IP20
Assembly details	Ceiling,Wall
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	800 mA
Safety class	II
Wattage	32 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Number of luminaires at LS B16A	20
Number of luminaires at LS C16A	32
Level of inrush current	48 A
Duration of inrush current	4 µs
Lumen	3700 lm
Colour temperature	3000 Kelvin
Beam angle	50 °
Color	black
CRI	90
UGR ≤	25
Service life	50000 h
Length	10.5 cm

2190383	

Height	14 cm
Diameter	10 cm
Net weight	0.72 kg
Gross weight	0.88 kg