


# TRACKSPOT C 3 Ph. 29W 940 50°

**Black**

The TRACKSPOT C 3-phase spotlight, which is compatible with S-Track and Eutrac systems, is the ideal choice for demanding commercial projects with a moderate budget, where high efficiency and the lowest possible energy consumption are the key points of focus. With an energy efficiency of over 145 lm/W, excellent colour rendering thanks to CRI 90, and a high luminous flux of up to 4,400 lumens, the luminaire offers a lighting solution that is perfect for small and large commercial areas. Thanks to a service life of 50,000 hours (L80B50), the TRACKSPOT C also ensures long-term reliability and reduces maintenance costs. Available in different versions with 17W or 29W, beam angles of 36° or 50°, in 3,000 K and 4,000 K, the TRACKSPOT C comes in black and white versions. This flexibility enables harmonious integration into different room concepts.




## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1008875 |
| **Number of different light outlets** | 1 |
| **IP Code** | IP20 |
| **Assembly details** | Ceiling,Wall |
| **Primary nominal voltage** | 220-240V ~50/60 Hz |
| **Secondary power / voltage** | 800 mA |
| **Safety class** | II |
| **Wattage** | 29 W |
| **Minimum ambient temperature** | -20 °C |
| **Maximum ambient temperature** | 35 °C |
| **Number of luminaires at LS B16A** | 15 |
| **Number of luminaires at LS C16A** | 24 |
| **Level of inrush current** | 65 A |
| **Duration of inrush current** | 400 µs |
| **Lumen** | 4200 lm |
| **Colour temperature** | 4000 Kelvin |
| **Beam angle** | 50 ° |
| **Color** | black |
| **CRI** | 90 |
| **UGR ≤** | 25 |
| **Service life** | 50000 h |
| **Length** | 10.5 cm |

| | |
|---|---|
| 2194011 |  |



| | |
|---|---|
| **Height** | 14 cm |
| **Diameter** | 10 cm |
| **Net weight** | 0.72 kg |
| **Gross weight** | 0.88 kg |