


CYFT DOME

wall- and ceiling-mounted light, 2700/3000/4000 K, 6.5 W, PHASE, black / milky

With its elegant design, the CYFT DOME wall and ceiling light blends harmoniously into quality interiors and sheltered outdoor areas. The timeless, round frosted glass shade provides a soft, even light distribution and gives the light its distinctive look. With protection class IP44, CYFT DOME is ideal for wet rooms such as bathrooms or covered outdoor areas. The integrated LED has a CRI >90 for particularly natural colour reproduction and can be flexibly adjusted via the CCT switch to 2,700 K, 3,000 K or 4,000 K - for atmospheric or functional lighting as required. Additional design freedom is provided by optional decorative rings in a range of trendy colours, which can be fitted without tools - including an extra robust rust effect version for outdoor area use.



TECHNICAL DATA

Item no.	1008944
IP Code	IP65
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Surface
Assembly details	Ceiling,Wall
Dimmable	Yes
Dimming technology	trailing edge
Number of through-wires	200
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	6.5 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	224
Number of luminaires at LS C16A	266
Level of inrush current	5 A
Duration of inrush current	100 µs
Lumen	290 / 310 / 310 lm
Colour temperature	2700/3000/4000 Kelvin
Color	black/milky

1807506	

Accessories

1008026	CYFT , decorative ring, matte nickel
1008025	CYFT , decorative ring, bronze
1007610	CYFT , decorative ring, brass
1008943	CYFT , decorative ring, rust
1007609	CYFT , decorative ring, chrome
1007611	CYFT , decorative ring, white

CRI	90
Service life	50000 h
Risk Group	0
Height	9.25 cm
Diameter	13.2 cm
Net weight	0.64 kg
Gross weight	0.96 kg