


NEW TRIA® 68

recessed ceiling light, PHASE, AIRTIGHT, round, 2700 K, 7.5 W, white

Discover the new generation of our NEW TRIA® recessed ceiling light. The NEW TRIA® 68 models are now also available in an airtight version, making them ideal for applications with increased airtightness requirements. The integrated LED module, available in 2,700K or 3,000K depending on the version, ensures maximum lighting design freedom. The high quality recessed light in black or white blends discreetly and stylishly into any ceiling.



TECHNICAL DATA

Item no.	1009020
IP Code	IP20/IP23
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Recessed
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	Leading edge,trailing edge
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	180 mA
Safety class	II
Wattage	7.5 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Number of luminaires at LS B16A	88
Number of luminaires at LS C16A	149
Level of inrush current	3 A
Duration of inrush current	30 µs
Lumen	591 lm
Colour temperature	2700 Kelvin
Beam angle	38 °
Color	white

869193	

CRI	90
UGR ≤	22
Service life	50000 h
Height	5.1 cm
Diameter	8.2 cm
Net weight	0.21 kg
Gross weight	0.24 kg
Shape of cut-out	round
Installation depth	4.8 cm
Installation diameter	6.8 cm
BIG WHITE Page	71