GRIP! M

Recessed ceiling light, PHASE, 2700 K, 42°, IP20, cylindrical, gold / black

GRIP! - the striking light family for sophisticated lighting design. With its distinctive knurled front ring and many new pendant, surface-mounted and recessed options, GRIP! now offers even more options for customised lighting concepts. The honeycomb louvre insert supplied as standard reduces glare and ensures optimum visual comfort. Different colours and designs blend harmoniously into living spaces, hotels or restaurants. High-quality technology with a CRI of 90, a lifetime of 50,000 hours and easy installation make GRIP! an all-round convincing choice.

TECHNICAL DATA

Item no.	1009090
Number of different light outlets	1
IP Code	IP20
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Recessed
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	500 mA
Safety class	II
Wattage	21 W
Minimum ambient temperature	0 °C
Maximum ambient temperature	35 °C
Number of luminaires at LS B16A	37
Number of luminaires at LS C16A	37
Level of inrush current	13.5 A
Duration of inrush current	26 µs
Lumen	2010 lm
Colour temperature	2700 Kelvin
Beam angle	42 °

2093822	

Accessories

1008495	GRIP! M , decorative ring, gold
1008494	GRIP! M , decorative ring, nickel
1008492	GRIP! M , decorative ring, white
1008493	GRIP! M , decorative ring, black

Color	black/black
CRI	90
Service life	50000 h
Risk Group	1
Length	18.2 cm
Height	6.4 cm
Diameter	4.3 cm
Net weight	0.356 kg
Gross weight	0.494 kg
Shape of cut-out	round
Installation depth	12.5 cm
Installation diameter	6.8 cm