
BATTEN P 1500 72

830/840/850 WH EM 3H

The BATTEN P light family from the SLVtec range offers powerful and flexible LED lighting solutions that are ideal for the energy-efficient refurbishment of existing T8/T5 fluorescent lamp installations. With a light output of up to 150lm/W and a lifespan of 100,000 hours (L80B10), they provide a durable, economical solution for commercial applications such as offices, schools, retail and infrastructure. The lights are available in three lengths (600, 1200, 1500 mm) and have an integrated multi-lumen and multi-CCT function: four output levels and three light colours (3,000/4,000/5,000 K) can be set on site using a DIP switch. Versions with integrated DALI control, sensors or emergency module (3h) are also available for maximum flexibility in lighting design. With its robust aluminium and polycarbonate (IP20, IK04) housing and simple assembly, the BATTEN P is ideal for demanding projects. An optional accessory 2m steel cable suspension kit completes the system and allows flexible mounting options such as ceiling or pendant mounting.



TECHNICAL DATA

Item no.	1009256
IP Code	IP20
Impact resistance class	IK 04
Assembly	Surface
Assembly details	Ceiling,Wall
Primary nominal voltage	220-240V ~0/50/60 Hz
Secondary power / voltage	200-350 mA
Safety class	I
Wattage	28 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	26
Number of luminaires at LS C16A	43
Level of inrush current	15 A
Duration of inrush current	272 µs
Lumen	4217 / 7316 lm
Colour temperature	3000/4000/5000 Kelvin
Color	white
CRI	80
Service life	100000 h
Risk Group	1
Length	150 cm

2432940	

Accessories

1009262	BATTEN P SCK2000 , 2000mm

Width	5.6 cm
Height	6.5 cm
Net weight	0.95 kg
Gross weight	1 kg