
NUMINOS® S

Recessed ceiling light, 2700 K, 40°, IP20, round, white

The NUMINOS light system from SLV combines technology, design and functionality like no other. This way, you can experience a thousand lighting design possibilities with a variety of downlights and spotlights. Also with the NUMINOS® DL S recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for unobtrusive, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light can convince with a power consumption of 6.7 watts, luminous flux of 1000 lumens, colour temperature of 2700 Kelvin and a high colour reproduction index of over 90. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?



TECHNICAL DATA

Item no.	1009446
Number of different light outlets	1
IP Code	IP20
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	200 mA
Safety class	III
Wattage	6.7 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	1000 lm
Colour temperature	2700 Kelvin
Beam angle	40 °
Color	white
CRI	90
UGR ≤	19
Service life	50000 h
Risk Group	1
Height	5.2 cm
Diameter	8 cm
Net weight	0.13 kg
Gross weight	0.23 kg

2093739	

Accessories

1010128	NUMINOS® S , reflector, copper
1010681	NUMINOS® S , frosted diffuser
1010682	NUMINOS® S , Elliptical diffuser
1010679	NUMINOS® S , Honey-comb diffuser
1010695	LED driver , 21W, 200 mA, DALI
1010703	LED driver , 23W, 200 mA, DALI
1010699	LED driver , 10W, 200 mA, PHASE
1010127	NUMINOS® S , reflector, gold
1010680	NUMINOS® S , Prismatic diffuser

Shape of cut-out	round
Installation depth	8 cm
Installation diameter	6.8 cm