
NUMINOS® GIMBLE L

Recessed ceiling light, 4000 K, 20°, IP20, round, white

The NUMINOS light system from SLV perfectly combines function, design and technology. This way, you can experience a thousand lighting design possibilities with a variety of downlights and spotlights. Also with the NUMINOS® GIMBLE L recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for harmonious, modern and space-saving lighting that directs the accent to objects or the room. Installation is then done in no time at all. When will you choose SLV's modular variety?



TECHNICAL DATA

Item no.	1009749
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
IP Code	IP20
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	500 mA
Safety class	III
Wattage	17 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	2700 lm
Colour temperature	4000 Kelvin
Beam angle	20 °
Color	white
CRI	90
UGR ≤	19
Service life	50000 h
Risk Group	1
Height	11.5 cm
Diameter	16 cm
Net weight	0.606 kg

2093752	

Accessories

1010689	NUMINOS® L , Frosted diffuser
1010132	NUMINOS® L , reflector, copper
1010697	LED driver , 21W, 500 mA
1010687	NUMINOS® L , Honey-comb diffuser
1010701	LED driver , 19 W, 500 mA, PHASE
1010688	NUMINOS® L , Prismatic diffuser
1010690	NUMINOS® L , Elliptical diffuser
1010131	NUMINOS® L , reflector, gold
1010705	LED driver , 36W, 500 mA, DALI

Gross weight	0.756 kg
Shape of cut-out	round
Installation depth	11.5 cm
Installation diameter	14.5 cm