
The NUMINOS light system from SLV combines technology, design and functionality like no other. This way, you can experience a thousand lighting design possibilities with a variety of downlights and spotlights. Like with the NUMINOS® MOVE DL L recessed ceiling light, which impresses with its high-quality workmanship and light. Ideal for harmonious, modern and space-saving lighting that directs the accent to objects or the room. The recessed ceiling light has a power consumption of 17 watts, a luminous flux of 2400 lumens, a colour temperature of 2700 Kelvin and a good colour reproduction index of over 90. This means that easy installation is a mere formality. When to choose NUMINOS from SLV – modular diversity awaits you.




## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1009812 |
| **Number of different light outlets** | 1 |
| **Rotating or tilting** | rotary bar and tiltable |
| **IP Code** | IP20 |
| **Assembly** | Recessed |
| **Assembly details** | Ceiling |
| **Secondary power / voltage** | 500 mA |
| **Safety class** | III |
| **Wattage** | 17 W |
| **Minimum ambient temperature** | -20 °C |
| **Maximum ambient temperature** | 40 °C |
| **Lumen** | 2400 lm |
| **Colour temperature** | 2700 Kelvin |
| **Beam angle** | 20 ° |
| **Color** | black/chrome |
| **CRI** | 90 |
| **UGR ≤** | 19 |
| **Service life** | 50000 h |
| **Risk Group** | 1 |
| **Height** | 9.3 cm |
| **Diameter** | 16 cm |
| **Net weight** | 0.51 kg |

## Light Source

| | |
|---|---|
| 2093870 |  |

## Accessories

| | |
|---|---|
| 1010689 | NUMINOS® L , Frosted diffuser |
| 1010697 | LED driver , 21W, 500 mA |
| 1010687 | NUMINOS® L , Honey-comb diffuser |
| 1010701 | LED driver , 19 W, 500 mA, PHASE |
| 1010688 | NUMINOS® L , Prismatic diffuser |
| 1010690 | NUMINOS® L , Elliptical diffuser |
| 1010705 | LED driver , 36W, 500 mA, DALI |
| 1010132 | NUMINOS® L , reflector, copper |
| 1010131 | NUMINOS® L , reflector, gold |

| | |
|---|---|
| **Gross weight** | 0.66 kg |
| **Shape of cut-out** | round |
| **Installation depth** | 10.5 cm |
| **Installation diameter** | 14.5 cm |