
NUMINOS® XL

Recessed ceiling light, 2700 K, 20°, IP20, round, white

The NUMINOS light system from SLV combines technology, design and functionality like no other. With different downlights and spotlights, you can experience a thousand lighting design possibilities. This also includes NUMINOS® DL XL, which impresses as a recessed ceiling light with the best workmanship and lighting quality. In this way, you can create discreet, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light can convince with a power consumption of 24 watts, luminous flux of 3500 lumens, colour temperature of 2700 Kelvin and a high colour reproduction index of over 90. This means that easy installation is a mere formality. When do you choose NUMINOS ® from SLV?



TECHNICAL DATA

Item no.	1009928
Number of different light outlets	1
IP Code	IP20
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	700 mA
Safety class	III
Wattage	24 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	3500 lm
Colour temperature	2700 Kelvin
Beam angle	20 °
Color	white
CRI	90
UGR ≤	19
Service life	50000 h
Risk Group	1
Height	10.5 cm
Diameter	16 cm
Net weight	0.704 kg
Gross weight	0.8 kg

2093865	

Accessories

1010698	LED driver , 30W, 700 mA
1010706	LED driver , 36W, 700 mA, DALI
1010694	NUMINOS® XL , Elliptical diffuser
1010133	NUMINOS® XL , reflector, gold
1010692	NUMINOS® XL , Prismatic diffuser
1010702	LED driver , 30W, 700 mA, PHASE
1010693	NUMINOS® XL , Frosted diffuser
1010134	NUMINOS® XL , reflector, copper
1010691	NUMINOS® XL , Honeycomb diffuser

Shape of cut-out	round
Installation depth	10.5 cm
Installation diameter	14.5 cm