
# FLATT II 62

**Free-standing lamp, PHASE, 2700 K, IP65, square, black**

The FLATT II light range combines modern design with high functionality. The wall-mounted and bollard lights are ideal for accentuated façade and path lighting. With a sea air resistant coating, dark sky compliant light distribution (ULOR <2%), 2,700K warm white light and optional sensor technology, they offer flexible solutions for residential and HoReCa applications.




## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1010106 |
| **Number of different light outlets** | 1 |
| **IP Code** | IP65 |
| **Impact resistance class** | IK 03 |
| **Impact resistance** | 0.35 Joule |
| **Assembly** | Surface |
| **Assembly details** | Ground |
| **Dimmable** | Yes |
| **Dimming technology** | Leading edge,trailing edge |
| **Number of through-wires** | 200 |
| **Primary nominal voltage** | 220-240V ~50/60 Hz |
| **Secondary power / voltage** | 240 mA |
| **Safety class** | I |
| **Wattage** | 10 W |
| **Minimum ambient temperature** | -25 °C |
| **Maximum ambient temperature** | 45 °C |
| **Number of luminaires at LS B16A** | 210 |
| **Number of luminaires at LS C16A** | 210 |
| **Level of inrush current** | 4.1 A |
| **Duration of inrush current** | 81 µs |
| **Temperature at glass (light emission)** | 75 °C |
| **Lumen** | 650 lm |

| | |
|---|---|
| |  |

## Accessories

| | |
|---|---|
| 228726 | Y-CONNECTION BOX , black, IP68 |
| 228730 | CONNECTION BOX , 3-pin, IP68 |

| | |
|---|---|
| **Colour temperature** | 2700 Kelvin |
| **Color** | black |
| **CRI** | 80 |
| **Service life** | 50000 h |
| **Risk Group** | 1 |
| **Length** | 18 cm |
| **Width** | 6 cm |
| **Height** | 62 cm |
| **Net weight** | 2.11 kg |
| **Gross weight** | 2.51 kg |