




FLATT II | WL, SENSOR

FLATT II, Wall-mounted light, SENSOR, 2700 K, 10W, anthracite / brown

The FLATT II is a square surface-mounted wall light, particularly suitable for use in indoor and covered outdoor areas where robust and functional lighting is required. It features an integrated sensor function that enables automatic control and allows the operation of additional luminaires without their own sensor. With a luminous flux of 640 lumens at a colour temperature of 2700 K and a maximum power consumption of 10 watts, it provides an efficient and pleasant light source. The housing is made of aluminium and is rated IP54 for protection against dust and splashing water, as well as impact resistance class IK03. The compact dimensions of approximately 26 cm height, 9.85 cm width, and 9.6 cm depth facilitate mounting on walls in various environments.



Light source

916561	A E

Item no.	1010107
Lamps included	No
Number of different light outlets	2
IP Code	IP54
Impact resistance class	IK03
Impact resistance	0.35 Joule
Assembly	Surface
Assembly details	Wall,
Number of through-wires	10
Primary nominal voltage	100-240V ~ 50/60Hz
Secondary power / voltage	240 mA
Safety class	I
Wattage	10 W
Minimum ambient temperature	-25°C
Maximum ambient temperature	45°C
Number of luminaires at LS B16A	210.0
Number of luminaires at LS C16A	210.0
Level of inrush current	12.8 A
Duration of inrush current	260 µs
Temperature at glass (light emission)	59
Beam angle	25°
Color	anthracite/brown
CRI	80
LXXBXX data	L80B20
Service life	50 000 h
Risk Group	1
Width	9.9 cm
Height	26 cm
Depth	9.6