

HELIA PRO S

Wall-mounted light, up/down, DALI, P1, cylindrical, 2700 K, 6W, 24°, white

The HELIA PRO wall light range offers flexible solutions for accentuating façades with two housing sizes and two wattage classes, either as single or up/down lighting. Efficient LED technology, DALI control, precise light distribution and resistance to sea air enable high-quality architectural lighting in outdoor areas.

TECHNICAL DATA

Item no.	1010164
Number of different light outlets	2
IP Code	IP65
Impact resistance class	IK 06
Impact resistance	1 Joule
Assembly	Surface
Assembly details	Wall
Dimmable	Yes
Dimming technology	DALI 2
Number of through-wires	15
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	400 mA
Safety class	I
Wattage	6 W
Minimum ambient temperature	-25 °C
Maximum ambient temperature	45 °C
Number of luminaires at LS B16A	15
Number of luminaires at LS C16A	24
Level of inrush current	65 A
Duration of inrush current	200 µs
Temperature at glass (light emission)	55 °C
Lumen	600 lm

	

Colour temperature	2700 Kelvin
Beam angle	24 °
Color	white
CRI	80
Service life	50000 h
Risk Group	1
Height	17.5 cm
Depth	6.5 cm
Diameter	6.5 cm
Net weight	0.87 kg
Gross weight	1.08 kg