

THEO PRO L

Wall-mounted light, single, DALI, P1, rectangular, 2700 K, 10W, 24°, white

The THEO PRO wall light series combines a clear, square design with modern technology for precise accent lighting. Available in two sizes and performance classes, with single or up/down light, they offer versatile solutions for modern façade lighting in outdoor areas thanks to DALI control and resistance to sea air.

TECHNICAL DATA

Item no.	1010186
Number of different light outlets	1
IP Code	IP65
Impact resistance class	IK 08
Impact resistance	5 Joule
Assembly	Surface
Assembly details	Wall
Dimmable	Yes
Dimming technology	DALI 2
Number of through-wires	15
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	250 mA
Safety class	I
Wattage	10 W
Ambient temperature	80 °C
Minimum ambient temperature	-25 °C
Maximum ambient temperature	45 °C
Number of luminaires at LS B16A	15
Number of luminaires at LS C16A	24
Level of inrush current	65 A
Duration of inrush current	200 µs
Lumen	1200 lm

	

Colour temperature	2700 Kelvin
Beam angle	24 °
Color	white
CRI	80
Service life	50000 h
Risk Group	1
Width	10.8 cm
Height	30.5 cm
Depth	15.5 cm
Net weight	1.82 kg
Gross weight	2.4 kg