
CYFT XL

wall- and ceiling-mounted light, 2700/3000/4000K, 15-W, PHASE, 125°, IP65 black / transparent

The CYFT WAVE wall and ceiling light - now also available in XL - brings a special touch to modern interiors with its striking, wave-shaped glass shade. With an IP65 protection code, it is ideal for wet rooms such as bathrooms and for protected indoor and outdoor areas. The integrated LED impresses with a colour rendering index CRI > 90 and a practical CCT switch, which allows the light colour to be flexibly adjusted between 2,700 K, 3,000 K and 4,000 K. Optional decorative rings in various trendy colours, which can be fitted without tools, provide even more design freedom - including a rust version especially for outdoor areas.



TECHNICAL DATA

Item no.	1010210
IP Code	IP65
Impact resistance class	IK 05
Impact resistance	0.7 Joule
Assembly	Surface
Assembly details	Ceiling,Wall
Dimmable	Yes
Dimming technology	trailing edge
Number of through-wires	50
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	15 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Number of luminaires at LS B16A	56
Number of luminaires at LS C16A	118
Level of inrush current	5 A
Duration of inrush current	300 µs
Lumen	810 / 920 / 930 lm
Colour temperature	2700/3000/4000 Kelvin
Beam angle	125 °

Accessories

1010213	CYFT XL , decorative ring, indoor, white
1010214	CYFT XL , decorative ring, indoor, brass
1010212	CYFT XL , decorative ring, outdoor, rust
1010215	CYFT XL , decorative ring, indoor, chrome

Color	black
CRI	90
Service life	50000 h
Risk Group	1
Height	7.2 cm
Diameter	20 cm
Net weight	2.75 kg
Gross weight	3.15 kg