


DYSKO | CW, DOUBLE, PHASE

DYSKO, CW, DOUBLE, PHASE, Wall and ceiling surface-mounted luminaire, 2700 K, 13 W, 36°, black

The DYSKO wall and ceiling surface-mounted luminaire is designed for indoor use and offers a colour temperature of 2700 K with a power consumption of 13 W. It produces a luminous flux of 1500 lumens with a beam angle of 36°. The housing is made of aluminium and measures 26.1 cm in length, 5.4 cm in width, and 6.8 cm in height. The luminaire features PHASE-cut dimming, allowing flexible control of light intensity. It has an IP20 protection rating and an IK02 impact resistance class. The luminaire is designed for a long service life of 50,000 hours.



Light source

2093820	A G D

Item no.	1010308
Lamps included	No
Number of different light outlets	2
IP Code	IP20
Impact resistance class	IK02
Impact resistance	0.2 Joule
Assembly	Surface
Assembly details	Ceiling,Wall,
Dimmable	true
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	150 mA
Safety class	I
Wattage	13 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	45°C
Number of luminaires at LS B16A	48.0
Number of luminaires at LS C16A	60.0
Level of inrush current	30 A
Duration of inrush current	30 µs
Beam angle	36°
Color	black
CRI	90
LXXBXX data	L80B10
Service life	50 000 h
Risk Group	1
Length	26.1 cm
Width	5.4 cm
Height	6.8 cm