


DYSKO | PD, PHASE

DYSKO, PD, PHASE, Pendant luminaire, 2700 K, 4.4 W, 36°, black

The DYSKO PD PHASE pendant light is designed for indoor use and is particularly suitable for ceiling mounting. It offers a luminous flux of 500 lumens with a colour temperature of 2700 K and a beam angle of 36°. The luminaire is equipped with phase-cut dimming, allowing stepless adjustment of the light intensity. The housing is made of aluminium and has a diameter of 5.4 cm with a height of 4.8 cm. The pendant length is 200 cm, providing flexible installation options. The IP20 protection rating and IK02 impact resistance ensure safe operation in protected indoor areas. The luminaire is designed as a ceiling recessed light and has a declared lifetime of 50,000 hours.



Light source

2093820	A to G: D

Item no.	1010361
Lamps included	No
Number of different light outlets	1
IP Code	IP20
Impact resistance class	IK02
Impact resistance	0.2 Joule
Assembly	Recessed
Assembly details	Ceiling,
Dimmable	true
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	100 mA
Safety class	II
Wattage	4 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	35°C
Number of luminaires at LS B16A	32.0
Number of luminaires at LS C16A	37.0
Level of inrush current	10 A
Duration of inrush current	300 µs
Beam angle	36°
Color	black
CRI	90
LXXBXX data	L80B10
Service life	50 000 h
Risk Group	1
Height	4.8 cm
Diameter	5.4 cm
Pendant length	200.0000 cm