# SIGHT EVO

**3~ Spot, DALI, single, rectangular, 3000K, 25W, 60°, white / black**

SIGHT EVO - the flexible 3-phase track spotlight series for perfect accent lighting. With single or double-flame spots, CCT options (3,000/4,000 K) and two total wattage options (18 W / 25 W), it provides the perfect setting for shops, galleries or showrooms. With UGR<19 and CRI>90, SIGHT EVO impresses with first-class light quality. The DALI option and uncomplicated installation make these lights perfect for versatile applications.

## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1010381 |
| **IP Code** | IP20 |
| **Impact resistance class** | IK 02 |
| **Impact resistance** | 0.2 Joule |
| **Assembly details** | Ceiling |
| **Dimmable** | Yes |
| **Dimming technology** | DALI |
| **Primary nominal voltage** | 220-240V ~50/60 Hz |
| **Secondary power / voltage** | 700 mA |
| **Safety class** | II |
| **Wattage** | 25 W |
| **Maximum ambient temperature** | 35 °C |
| **Number of luminaires at LS B16A** | 21 |
| **Number of luminaires at LS C16A** | 34 |
| **Level of inrush current** | 45 A |
| **Duration of inrush current** | 280 µs |
| **Lumen** | 3200 lm |
| **Colour temperature** | 3000 Kelvin |
| **Beam angle** | 60 ° |
| **Color** | white/black |
| **CRI** | 90 |
| **UGR ≤** | 16 |

| | |
|---|---|
| |  |

| | |
|---|---|
| **Service life** | 50000 h |
| **Risk Group** | 1 |
| **Length** | 117.5 cm |
| **Width** | 4.1 cm |
| **Height** | 4 cm |
| **Net weight** | 0.84 kg |
| **Gross weight** | 1.32 kg |