DOWNLIGHT VARIO 220 22 830/840 WH ML

DOWNLIGHT VARIA is your all-round lighting solution. A round, minimalist design. Available in two diameters: 22 cm and 29 cm. Easy to install. Equipped with a CCT switch, you can select your ideal colour temperature (3000 K and 4000 K). The wattage control allows you to easily adjust the light intensity - up to 3000 lumens for the 29cm version. There are also two models: on/off and with PIR sensor.

TECHNICAL DATA

Item no.	1010397
Number of different light outlets	1
IP Code	IP20
Impact resistance class	IK 03
Assembly	Recessed
Assembly details	Ceiling
Number of through-wires	30
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	100/190 mA
Safety class	II
Wattage	9 W
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	36
Number of luminaires at LS C16A	60
Level of inrush current	18 A
Duration of inrush current	100 µs
Lumen	1150 / 1200 / 2200 / 2250 lm
Colour temperature	3000/4000/3000/4000 Kelvin
Beam angle	110 °
Color	white
CRI	80
UGR ≤	28

	

Service life	50000 h
Risk Group	1
Height	2.2 cm
Diameter	21.7 cm
Net weight	0.45 kg
Gross weight	0.59 kg
Shape of cut-out	TBD
Installation depth	3 cm
Installation diameter	19.5 cm