

WATERPROOF V

1200 41 830/840/850 ML DALI IP66

The WATERPROOF moisture-proof luminaire offers energy-efficient lighting solutions in three performance classes, with up to 180 lm/W, IP66, IK08 and a service life of up to 100,000 hours. Thanks to tool-free cap opening and integrated through-wiring, installation is particularly quick. Optionally with DALI and sensor - ideal for industry, warehouses or underground car parks.



TECHNICAL DATA

Item no.	1010838
IP Code	IP65
Impact resistance class	IK 08
Assembly	Surface
Assembly details	Ceiling,Wall
Dimmable	Yes
Dimming technology	DALI
Primary nominal voltage	220-240V ~0/50/60 Hz
Secondary power / voltage	200-350 mA
Safety class	I
Wattage	16 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	41
Number of luminaires at LS C16A	66
Level of inrush current	27.8 A
Duration of inrush current	150 µs
Lumen	2149 / 3892 lm
Colour temperature	3000/4000/5000 Kelvin
Beam angle	120 °
Color	white
CRI	80

	

Service life	50000 h
Risk Group	1
Length	120 cm
Width	8.3 cm
Height	8.2 cm
Net weight	1.37 kg
Gross weight	1.49 kg