


# EURO CUBE 2 L | DALI

**EURO CUBE 2 L, 3-phase spotlight, rectangular, 3000K, 21 W, DALI 2, 40°, black**

The EURO CUBE 2 3-phase spotlight stands out with its striking, rectangular design and high light quality. With 14 W or 21 W, up to 2400 lm, CRI >90 and a 40° beam angle, it is ideal for accent and zoned general lighting. Thanks to the integrated CCT switch (3000 K/4000 K) and PHASE or DALI dimming, it offers outstanding flexibility. In black or white, optionally with accessories such as honeycomb louvre or oval filter.




## Light source

| | |
|---|---|
| 2093831 | A G D |

## Accessories

| | |
|---|---|
| 1010858 | EURO CUBE 2 L, HONEYCOMB |
| 1010859 | EURO CUBE 2 L, OVAL FILTER |

| | |
|---|---|
| Item no. | 1010854 |
| Number of different light outlets | 1 |
| IP Code | IP20 |
| Impact resistance class | IK02 |
| Impact resistance | 0.2 Joule |
| Assembly | Track |
| Assembly details | Ceiling, |
| Dimmable | true |
| Dimming technology | DALI 2 |
| Primary nominal voltage | 220-240V ~ 50/60Hz |
| Secondary power / voltage | 550 mA |
| Safety class | II |
| Wattage | 21 W |
| Maximum ambient temperature | 35°C |
| Number of luminaires at LS B16A | 96.0 |
| Number of luminaires at LS C16A | 154.0 |
| Level of inrush current | 10 A |
| Duration of inrush current | 3 µs |
| Beam angle | 40° |
| Color | black |
| CRI | 90 |
| UGR ≤ | 19 |
| LXXBXX data | L90B10 |
| Service life | 50 000 h |
| Risk Group | 1 |
| Length | 19.8 cm |
| Width | 6.9 cm |
| Height | 14.5 cm |
| Net weight | 0.7 kg |