

# BATTEN FLAT P

**1500 72 830/840/850 ML Microwave WH**

BATTEN FLAT P - the robust IP44 solution for multi-storey car parks, corridors/hallways or plant rooms. The multi-lumen and multi-CCT function (3,000/4,000/5,000 K) allows the light output to be flexibly adjusted. Variants with DALI2 control or integrated HF motion sensor automatically activate the light only when there is movement, thus enabling energy-saving, intelligent operation. The end caps, which can be opened without tools, simplify maintenance and installation.




## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1010918 |
| **IP Code** | IP44 |
| **Impact resistance class** | IK 04 |
| **Impact resistance** | 0.5 Joule |
| **Assembly** | Surface |
| **Assembly details** | Ceiling,Wall |
| **Number of through-wires** | 51 |
| **Primary nominal voltage** | 220-240V ~0/50/60 Hz |
| **Secondary power / voltage** | 200-350 mA |
| **Safety class** | I |
| **Wattage** | 29 W |
| **Minimum ambient temperature** | -20 °C |
| **Maximum ambient temperature** | 40 °C |
| **Number of luminaires at LS B16A** | 24 |
| **Number of luminaires at LS C16A** | 40 |
| **Level of inrush current** | 19.23 A |
| **Duration of inrush current** | 240 µs |
| **Lumen** | 4331 / 7700 lm |
| **Colour temperature** | 3000/4000/5000 Kelvin |
| **Beam angle** | 120 ° |
| **Color** | white |
| **CRI** | 80 |

| | |
|---|---|
| 2481885 |  |
| |  |

## Accessories

| | |
|---|---|
| 1010932 | BATTEN FLAT P , Suspension kits with 2m 2pcs |
| 1010931 | BATTEN FLAT P , Wall brackets, 2pcs |
| 1011005 | BATTEN FLAT P , remote control PIR sensor |
| 1010933 | BATTEN FLAT P , Horizontal cable wire suspension kits, 2pcs |

| | |
|---|---|
| **UGR ≤** | 25 |
| **Service life** | 100000 h |
| **Risk Group** | 1 |
| **Length** | 148.6 cm |
| **Width** | 15.2 cm |
| **Height** | 5.2 cm |
| **Net weight** | 3.76 kg |
| **Gross weight** | 4.22 kg |