


# UNIVERSAL DOWN-LIGHT MOVE

**recessed luminaire with cover, PHASE, 2700/3000/4000/6500K, IP20, swivelling, white**

Many qualities in one-this is how the SLV UNIVERSAL DOWNLIGHT is designed. The colour temperature can be quickly adjusted in four stages via CCT switch. The choice of 5 W or 7 W output is just as simple. And thanks to the lockable springs and Quick Connector Box, the downlight is quick and easy to install. In addition, the separately available covers in round or square and various colours allow the UNIVERSAL DOWNLIGHT to be used as a fixed downlight with IP65 or as a swivelling downlight with IP20. A suitable cover is included in the scope of delivery and ensures immediate readiness for use.




## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1011210 |
| **Rotating or tilting** | tiltable |
| **IP Code** | IP20 |
| **Impact resistance class** | IK 02 |
| **Impact resistance** | 0.2 Joule |
| **Assembly** | Recessed |
| **Assembly details** | Ceiling |
| **Dimmable** | Yes |
| **Dimming technology** | trailing edge |
| **Number of through-wires** | 10 |
| **Primary nominal voltage** | 220-240V ~50/60 Hz |
| **Secondary power / voltage** | 60 mA |
| **Safety class** | II |
| **Wattage** | 5 W |
| **Maximum ambient temperature** | 40 °C |
| **Number of luminaires at LS B16A** | 80 |
| **Number of luminaires at LS C16A** | 200 |
| **Level of inrush current** | 3 A |
| **Duration of inrush current** | 30 µs |
| **Lumen** | 670 / 680 / 690 / 680 lm |
| **Colour temperature** | 2700/3000/4000/6500 Kelvin |
| **Beam angle** | 38 ° |

| | |
|---|---|
| 2093260 |  |

## Accessories

| | |
|---|---|
| 1007187 | UNIVERSAL DOWN-LIGHT cover , for down-light IP20, pivoting, square, gold |
| 1007094 | UNIVERSAL DOWN-LIGHT Cover , for Down-light IP20, pivoting, round, gold |
| 1007186 | UNIVERSAL DOWN-LIGHT cover , for down-light IP20, pivoting, square, aluminium |
| 1007091 | UNIVERSAL DOWN-LIGHT Cover , for Down-light IP20, pivoting, round, black |
| 1007093 | UNIVERSAL DOWN-LIGHT Cover , for Down-light IP20, pivoting, round, aluminium |
| 1007194 | UNIVERSAL DOWN-LIGHT cover , for down-light IP20, pivoting, square, gold matt |
| 1007185 | UNIVERSAL DOWN-LIGHT cover , for down-light IP20, pivoting, square, white |
| 1007184 | UNIVERSAL DOWN-LIGHT cover , for down-light IP20, pivoting, square, black |

| | |
|---|---|
| **Color** | white |
| **CRI** | 90 |
| **Service life** | 50000 h |
| **Risk Group** | 1 |
| **Height** | 6.2 cm |
| **Diameter** | 8.8 cm |
| **Net weight** | 0.278 kg |
| **Gross weight** | 0.33 kg |
| **Shape of cut-out** | round |
| **Installation depth** | 7 cm |
| **Installation diameter** | 6.8 cm |