


EASYLIGHT 2500 140 835/840/850 NB WH ML EM 3H | TRUNKING SYSTEM 2500MM

EASYLIGHT 2500 140 835/840/850 NB WH ML EM 3H Trunking System 2500MM

The EASYLIGHT 2500 140 835/840/850 NB WH ML EM 3H light strip system is designed for use in commercial and industrial indoor spaces. It offers a flexible lighting solution with variable luminous flux ranging from 5600 to 15800 lumens. The housing is made of aluminium, and the cover is made of PMMA, ensuring a robust and durable construction. With a length of 250 cm, a width of 6.5 cm, and a height of 6.8 cm, the system is intended for installation in trunking systems. The IP20 protection rating and IK06 impact resistance class guarantee safe operation in protected environments. The luminaire is available in several light colours with colour temperatures of 3500 K, 4000 K, and 5000 K, making it suitable for a wide range of lighting requirements.



Item no.	1011239
IP Code	IP20
Impact resistance class	IK06
Primary nominal voltage	220-240V ~ 0/50/60Hz
Secondary power / voltage	200-550mA
Safety class	I
Wattage	29 W
Ambient temperature	80
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	21.0
Number of luminaires at LS C16A	34.0
Level of inrush current	19.81 A
Duration of inrush current	268 µs
Color	white
CRI	80
UGR ≤	25
LXXBXX data	L80B10
Service life	100 000 h
Risk Group	1
Length	250 cm
Width	6.5 cm
Height	6.8 cm
Net weight	4.09 kg
Gross weight	4.38 kg

Accessories

1009230	EASYLIGHT, FIB 300 5 25 WH Feed in Box 300mm, 5 pole, 2.5mm2
1009232	EASYLIGHT, FOB 300 5 25 WH Feed out Box 300mm, 5 pole, 2.5mm2
1009232	EASYLIGHT, FOB 300 5 25 WH Feed out Box 300mm, 5 pole, 2.5mm2
1009236	EASYLIGHT, BC 2500 5 25 WH Blind Cover 2500mm, 5 pole, 2.5mm2
1009238	EASYLIGHT, BC 4500 5 25 WH Blind Cover 4500mm, 5 pole, 2.5mm2
1009240	EASYLIGHT, EC WH End Cap white
1009241	EASYLIGHT, CSK Chain suspension kits (without chain)
1009242	EASYLIGHT, CSK FT Chain suspension kits fine tuned (without chain)
1009244	EASYLIGHT, SCF M6 Surface ceiling fix M6
1009245	EASYLIGHT, SCF M10, Surface ceiling fix M10
1009246	EASYLIGHT, STM Surface Track mounted
1009247	EASYLIGHT, SCK 5000 Steel cable suspension kits 5000mm