


# TRACK PANEL 3PH. 120 830/840 | WB ML BK DALI

**TRACK PANEL, 3PH. 120 830/840 WB ML BK DALI**

The TRACK PANEL is a wide-area LED solution for 3-phase tracks and is ideal for uniform, low-glare general lighting in retail, office and commercial areas. With multi-lumen and multi-colour function and optional DALI control, it enables flexible adaptation to project-specific requirements.




| | |
|---|---|
| Item no. | 1011399 |
| IP Code | IP20 |
| Impact resistance class | IK02 |
| Impact resistance | 0.2 Joule |
| Assembly | Track |
| Assembly details | Ceiling, |
| Dimmable | true |
| Dimming technology | DALI 2 |
| Primary nominal voltage | 220-240V ~ 50/60Hz |
| Secondary power / voltage | 200/250/300/350mA |
| Safety class | I |
| Wattage | 39 W |
| Minimum ambient temperature | -20°C |
| Maximum ambient temperature | 40°C |
| Number of luminaires at LS B16A | 19.0 |
| Number of luminaires at LS C16A | 31.0 |
| Level of inrush current | 22.18 A |
| Duration of inrush current | 262 µs |
| Beam angle | 90° |
| Color | black |
| CRI | 80 |
| Binning | 3.0000 |
| LXXBXX data | L80B10 |
| Service life | 100 000 h |
| Length | 57.8 cm |
| Width | 18.9 cm |
| Height | 10.5 cm |
| Net weight | 2.93 kg |
| Gross weight | 3.4 kg |