


TUBULAR P 1200 530 830 | WH DALI2 OPL PMMA

TUBULAR P, 1200 530 830 WH DALI2 OPL PMMA

The TUBULAR P wet room luminaire is designed for use in demanding environments with high humidity and dust exposure. It delivers a luminous flux of 5600 lumens and has a declared service life of 100,000 hours. The housing is equipped with a PMMA diffuser and measures 115 cm in length with a diameter of 7.5 cm. The luminaire features a DALI 2 dimming function, allowing flexible light control. With an IP66/IP69K protection rating, it offers high protection against dust ingress and powerful water jets. The impact resistance corresponds to the IK07 class, emphasising its robust construction. This wet room luminaire is particularly suitable for industrial and commercial applications where reliable and durable lighting is required.



Item no.	1011474
IP Code	IP66/IP69K
Impact resistance class	IK07
Dimmable	true
Dimming technology	DALI 2
Primary nominal voltage	220-240V ~ 0/50/60Hz
Secondary power / voltage	300 mA
Safety class	I
Wattage	35 W
Ambient temperature	80
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	30.0
Number of luminaires at LS C16A	49.0
Level of inrush current	17 A
Duration of inrush current	30 µs
Beam angle	120°
Color	white
CRI	80
UGR ≤	27
LXXBXX data	L80B10
Service life	100 000 h
Risk Group	1
Length	115 cm
Diameter	7.5 cm
Net weight	1.51 kg
Gross weight	1.55 kg