


TUBULAR P 1200 560 840 | WH DALI2 OPL PMMA

TUBULAR P, 1200 560 840 WH DALI2 OPL PMMA

The TUBULAR P damp-proof luminaire is designed for use in demanding environments with high moisture exposure. It has a length of 115 cm and a diameter of 7.5 cm. The luminaire delivers a luminous flux of 5900 lumens and is equipped with DALI 2 dimming technology, allowing flexible light control. The housing is made of plastic and features a PMMA opal diffuser, which ensures uniform light distribution. The IP66/IP69K protection rating guarantees high protection against dust and water ingress, while the IK07 impact resistance confirms a robust construction. These features make the TUBULAR P a suitable solution for damp rooms and industrial applications.



Item no.	1011475
IP Code	IP66/IP69K
Impact resistance class	IK07
Dimmable	true
Dimming technology	DALI 2
Primary nominal voltage	220-240V ~ 0/50/60Hz
Secondary power / voltage	300 mA
Safety class	I
Wattage	35 W
Ambient temperature	80
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	30.0
Number of luminaires at LS C16A	49.0
Level of inrush current	17 A
Duration of inrush current	30 µs
Beam angle	120°
Color	white
CRI	80
UGR ≤	27
LXXBXX data	L80B10
Service life	100 000 h
Risk Group	1
Length	115 cm
Diameter	7.5 cm
Net weight	1.51 kg
Gross weight	1.55 kg