


TUBULAR P 1500 760 830 | WH DALI2 OPL PMMA

TUBULAR P, 1500 760 830 WH DALI2 OPL PMMA

The TUBULAR P damp-proof luminaire is designed for use in demanding environments where protection against dust and water is required. It features a high protection rating of IP66/IP69K and an impact resistance class of IK07, making it robust against mechanical influences. With a length of 145 cm and a diameter of 7.5 cm, the luminaire delivers a luminous flux of 7,900 lumens. The housing is made of plastic, and the cover is manufactured from PMMA. The luminaire is equipped with DALI 2 dimming, allowing flexible control of light intensity. The TUBULAR P is particularly suitable for damp rooms and industrial applications where reliable and durable lighting is needed.



Item no.	1011477
IP Code	IP66/IP69K
Impact resistance class	IK07
Dimmable	true
Dimming technology	DALI 2
Primary nominal voltage	220-240V ~ 0/50/60Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	50 W
Ambient temperature	80
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	19.0
Number of luminaires at LS C16A	31.0
Level of inrush current	20 A
Duration of inrush current	19 µs
Beam angle	120°
Color	white
CRI	80
UGR ≤	27
LXXBXX data	L80B10
Service life	100 000 h
Risk Group	1
Length	145 cm
Diameter	7.5 cm
Net weight	1.76 kg
Gross weight	1.8 kg