


TUBULAR P 1500 800 850 | WH DALI2 OPL PMMA

TUBULAR P, 1500 800 850 WH DALI2 OPL PMMA

The TUBULAR P is a damp-proof luminaire designed for use in demanding environments with high humidity and dust. It is particularly suitable for industrial and commercial applications where robust and reliable lighting is required. The luminaire provides a light output of 8500 lumens and features a DALI 2 dimming function, allowing flexible control. The housing is made of plastic with a PMMA diffuser, ensuring uniform light distribution. With a length of 145 cm and a diameter of 7.5 cm, the luminaire offers a compact design. The IP66/IP69K protection rating guarantees high resistance against water and dust, while the IK07 impact resistance class absorbs mechanical stresses. The TUBULAR P is thus a durable and functional solution for damp-proof lighting.



Item no.	1011479
IP Code	IP66/IP69K
Impact resistance class	IK07
Dimmable	true
Dimming technology	DALI 2
Primary nominal voltage	220-240V ~ 0/50/60Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	50 W
Ambient temperature	80
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	19.0
Number of luminaires at LS C16A	31.0
Level of inrush current	20 A
Duration of inrush current	19 µs
Beam angle	120°
Color	white
CRI	80
UGR ≤	27
LXXBXX data	L80B10
Service life	100 000 h
Risk Group	1
Length	145 cm
Diameter	7.5 cm
Net weight	1.76 kg
Gross weight	1.8 kg