


TUBULAR P 1500 880 830 | WH DALI2 CLR PMMA

TUBULAR P, 1500 880 830 WH DALI2 CLR PMMA

The TUBULAR P damp-proof luminaire is designed for use in demanding environments where high protection ratings are required. It delivers a light output of 9,000 lumens and features DALI 2 dimming, allowing for flexible light control. The housing is made of a plastic material with a PMMA optic and measures 145 cm in length with a diameter of 7.5 cm. The luminaire has a high protection rating of IP66/IP69K against dust and water ingress, as well as an impact resistance rating of IK07, making it robust against mechanical impacts. The long declared service life of 100,000 hours underlines its suitability for durable installations in damp rooms.



Item no.	1011480
IP Code	IP66/IP69K
Impact resistance class	IK07
Dimmable	true
Dimming technology	DALI 2
Primary nominal voltage	220-240V ~ 0/50/60Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	50 W
Ambient temperature	80
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	19.0
Number of luminaires at LS C16A	31.0
Level of inrush current	20 A
Duration of inrush current	19 µs
Beam angle	90°
Color	white
CRI	80
UGR ≤	27
LXXBXX data	L80B10
Service life	100 000 h
Risk Group	1
Length	145 cm
Diameter	7.5 cm
Net weight	1.96 kg
Gross weight	2 kg