


TUBULAR P 1500 930 840 | WH DALI2 CLR PMMA

TUBULAR P, 1500 930 840 WH DALI2 CLR PMMA

The TUBULAR P wet room luminaire is designed for use in demanding environments with high humidity. It features a luminous flux of 9600 lumens and a declared service life of 100,000 hours. The housing is made of plastic and equipped with a PMMA cover. The luminaire measures 145 cm in length and has a diameter of 7.5 cm. It is equipped with a DALI 2 dimming function, allowing flexible light control. The IP66/IP69K protection rating ensures high protection against dust and water ingress, while the impact resistance corresponds to IK07 class. This combination of robust design and powerful control makes the luminaire suitable for industrial and commercial applications in wet rooms.



Item no.	1011481
IP Code	IP66/IP69K
Impact resistance class	IK07
Dimmable	true
Dimming technology	DALI 2
Primary nominal voltage	220-240V ~ 0/50/60Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	58 W
Ambient temperature	80
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	19.0
Number of luminaires at LS C16A	31.0
Level of inrush current	20 A
Duration of inrush current	19 µs
Beam angle	90°
Color	white
CRI	80
UGR ≤	27
LXXBXX data	L80B10
Service life	100 000 h
Risk Group	1
Length	145 cm
Diameter	7.5 cm
Net weight	1.96 kg
Gross weight	2 kg