


TUBULAR P 1200 470 830 | WH DALI2 OPL PC

TUBULAR P, 1200 470 830 WH DALI2 OPL PC

The TUBULAR P damp-proof luminaire is designed for use in demanding environments where high protection ratings are required. It features a robust polycarbonate cover and offers reliable protection against dust and powerful jet water with an IP66/IP69K rating. With a length of 115 cm and a diameter of 7.5 cm, it is compactly constructed. The luminaire delivers a luminous flux of 5000 lumens and is equipped with DALI 2 dimming, enabling flexible light control. Its high impact resistance is classified as IK10, making it resistant to mechanical influences. The TUBULAR P is particularly suitable for damp rooms and areas with high requirements for protection and robustness.



Item no.	1011523
IP Code	IP66/IP69K
Impact resistance class	IK10
Dimmable	true
Dimming technology	DALI 2
Primary nominal voltage	220-240V ~ 0/50/60Hz
Secondary power / voltage	300 mA
Safety class	I
Wattage	35 W
Ambient temperature	80
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	30.0
Number of luminaires at LS C16A	49.0
Level of inrush current	17 A
Duration of inrush current	222 µs
Beam angle	120°
Color	white
CRI	80
UGR ≤	27
LXXBXX data	L80B10
Service life	100 000 h
Risk Group	1
Length	115 cm
Diameter	7.5 cm
Net weight	1.51 kg
Gross weight	1.55 kg