


WORKLIGHT P LINE 1200 52 830/840 WB ML | DALI DT8 WH

WORKLIGHT P LINE, 1200 52 830/840 WB ML DALI DT8 WH

The WORKLIGHT P LINE is a powerful LED pendant luminaire for use in office and work environments. With UGR < 19 and harmonised direct/indirect light distribution, it ensures high visual comfort and uniform illumination of workstations. Multi-lumen and multi-colour functionality enables adjustment of luminous flux and colour temperature. The DALI DT8 interface allows separate control of brightness and light colour and ensures integration into modern lighting management systems.



Item no.	1011574
IP Code	IP20
Impact resistance class	IK02
Assembly	Surface
Assembly details	Ceiling,Wall,
Dimmable	true
Dimming technology	DALI 2
Primary nominal voltage	220-240V ~ 0/50/60Hz
Secondary power / voltage	630-1200
Safety class	I
Wattage	26 W
Ambient temperature	80
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	32.0
Number of luminaires at LS C16A	32.0
Level of inrush current	15.5 A
Duration of inrush current	198 µs
Beam angle	90°
Color	white
CRI	80
UGR ≤	19
LXXBXX data	L80B10
Service life	100 000 h
Risk Group	1
Length	120 cm
Width	16 cm
Height	5 cm
Pendant length	200.0000 cm