


# WORKLIGHT P LINE 1200 52 830/840 WB ML | DALI DT8 BK

**WORKLIGHT P LINE, 1200 52 830/840 WB ML DALI DT8 BK**

The WORKLIGHT P LINE is a powerful LED pendant luminaire for use in office and work environments. With UGR < 19 and harmonised direct/indirect light distribution, it ensures high visual comfort and uniform illumination of workstations. Multi-lumen and multi-colour functionality enables adjustment of luminous flux and colour temperature. The DALI DT8 interface allows separate control of brightness and light colour and ensures integration into modern lighting management systems.




| | |
|---|---|
| Item no. | 1011575 |
| IP Code | IP20 |
| Impact resistance class | IK02 |
| Assembly | Surface |
| Assembly details | Ceiling,Wall, |
| Dimmable | true |
| Dimming technology | DALI 2 |
| Primary nominal voltage | 220-240V ~ 0/50/60Hz |
| Secondary power / voltage | 630-1200 |
| Safety class | I |
| Wattage | 26 W |
| Ambient temperature | 80 |
| Minimum ambient temperature | -20°C |
| Maximum ambient temperature | 40°C |
| Number of luminaires at LS B16A | 32.0 |
| Number of luminaires at LS C16A | 32.0 |
| Level of inrush current | 15.5 A |
| Duration of inrush current | 198 µs |
| Beam angle | 90° |
| Color | black |
| CRI | 80 |
| UGR ≤ | 19 |
| LXXBXX data | L80B10 |
| Service life | 100 000 h |
| Risk Group | 1 |
| Length | 120 cm |
| Width | 16 cm |
| Height | 5 cm |
| Pendant length | 200.0000 cm |