


TRACK LINE S 3PH. 40 830/835/840 DWB ML | WH

TRACK LINE S, 3~ Spot, 40 830/835/840 DWB ML WH

The TRACK LINE S 3~ spot is a three-phase spotlight suitable for indoor use, for example in showrooms, retail spaces, or office environments. The luminaire offers a light output ranging from 2500 to 4100 lumens and is available in various colour temperatures (830, 835, 840) with asymmetric light distribution (DWB). The housing is made of aluminium combined with a PMMA cover. With a width of 6.47 cm, a length of 57.8 cm, and a height of 7 cm, the product is compactly designed. The IP20 protection rating and IK02 impact resistance provide adequate protection against foreign objects and mechanical impacts. This lighting system is designed for use on three-phase track systems and allows flexible adjustment of the light source.



Item no.	1011580
IP Code	IP20
Impact resistance class	IK02
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	200-350mA
Safety class	I
Wattage	14 W
Ambient temperature	80
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	31.0
Number of luminaires at LS C16A	51.0
Level of inrush current	12.62 A
Duration of inrush current	276 µs
Beam angle	120°
Color	white
CRI	80
LXXBXX data	L80B10
Service life	100 000 h
Length	57.8 cm
Width	6.5 cm
Height	7 cm
Net weight	0.71 kg
Gross weight	0.81 kg