


TRACK LINE S 3PH. 40 830/835/840 DWB ML | WH DALI

TRACK LINE S, 3~ Spot, 40 830/835/840 DWB ML WH DALI

The TRACK LINE S 3~ spot is a three-phase spotlight designed for indoor use. Typical applications include commercial and public spaces where flexible and targeted lighting is required. The luminaire features a DALI dimming function, enabling precise light control. It offers a luminous flux ranging from 2400 to 4100 lumens and is equipped with an aluminium housing and PMMA optics. The dimensions are 57.8 cm in length, 6.47 cm in width, and 7 cm in height. The IP20 protection rating and IK02 impact resistance provide basic protection against foreign objects and mechanical impacts. The combination of robust materials and flexible control makes this spot suitable for professional installations in a variety of indoor scenarios.



Item no.	1011581
IP Code	IP20
Impact resistance class	IK02
Dimmable	true
Dimming technology	DALI 2
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	200-350mA
Safety class	I
Wattage	15 W
Ambient temperature	80
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	19.0
Number of luminaires at LS C16A	32.0
Level of inrush current	16.63 A
Duration of inrush current	330 µs
Beam angle	120°
Color	white
CRI	80
LXXBXX data	L80B10
Service life	100 000 h
Length	57.8 cm
Width	6.5 cm
Height	7 cm
Net weight	0.71 kg
Gross weight	0.81 kg